



Tanium™ End-User Notifications User Guide

Version 1.9.12

September 14, 2021

The information in this document is subject to change without notice. Further, the information provided in this document is provided “as is” and is believed to be accurate, but is presented without any warranty of any kind, express or implied, except as provided in Tanium’s customer sales terms and conditions. Unless so otherwise provided, Tanium assumes no liability whatsoever, and in no event shall Tanium or its suppliers be liable for any indirect, special, consequential, or incidental damages, including without limitation, lost profits or loss or damage to data arising out of the use or inability to use this document, even if Tanium Inc. has been advised of the possibility of such damages.

Any IP addresses used in this document are not intended to be actual addresses. Any examples, command display output, network topology diagrams, and other figures included in this document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

Please visit <https://docs.tanium.com> for the most current Tanium product documentation.

This documentation may provide access to or information about content, products (including hardware and software), and services provided by third parties (“Third Party Items”). With respect to such Third Party Items, Tanium Inc. and its affiliates (i) are not responsible for such items, and expressly disclaim all warranties and liability of any kind related to such Third Party Items and (ii) will not be responsible for any loss, costs, or damages incurred due to your access to or use of such Third Party Items unless expressly set forth otherwise in an applicable agreement between you and Tanium.

Further, this documentation does not require or contemplate the use of or combination with Tanium products with any particular Third Party Items and neither Tanium nor its affiliates shall have any responsibility for any infringement of intellectual property rights caused by any such combination. You, and not Tanium, are responsible for determining that any combination of Third Party Items with Tanium products is appropriate and will not cause infringement of any third party intellectual property rights.

Tanium is committed to the highest accessibility standards for our products. To date, Tanium has focused on compliance with U.S. Federal regulations - specifically Section 508 of the Rehabilitation Act of 1998. Tanium has conducted 3rd party accessibility assessments over the course of product development for many years and has most recently completed certification against the WCAG 2.1 / VPAT 2.3 standards for all major product modules in summer 2021. In the recent testing the Tanium Console UI achieved supports or partially supports for all applicable WCAG 2.1 criteria. Tanium can make available any VPAT reports on a module-by-module basis as part of a larger solution planning process for any customer or prospect.

As new products and features are continuously delivered, Tanium will conduct testing to identify potential gaps in compliance with accessibility guidelines. Tanium is committed to making best efforts to address any gaps quickly, as is feasible, given the severity of the issue and scope of the changes. These objectives are factored into the ongoing delivery schedule of features and releases with our existing resources.

Tanium welcomes customer input on making solutions accessible based on your Tanium modules and assistive technology requirements. Accessibility requirements are important to the Tanium customer community and we are committed to prioritizing these compliance efforts as part of our overall product roadmap. Tanium maintains transparency on our progress and milestones and welcomes any further questions or discussion around this work. Contact your sales representative, email Tanium Support at support@tanium.com, or email accessibility@tanium.com to make further inquiries.

Tanium is a trademark of Tanium, Inc. in the U.S. and other countries. Third-party trademarks mentioned are the property of their respective owners.

© 2021 Tanium Inc. All rights reserved.

Table of contents

- End-User Notifications overview** 5
 - End-User Notifications 5
 - End-User Self Service 5
 - Integration with other Tanium products 5
 - Deploy 5
 - Patch 5
 - Enforce 5
- Getting started** 6
 - Step 1: Install and configure Tanium End-User Notifications 6
 - Step 2: Configure endpoint restart notifications for Deploy or Patch deployments 6
 - Step 3: Configure notifications for Enforce FileVault or BitLocker policies 6
 - Step 4: Customize the end-user interface to use with Deploy 6
- End-User Notifications requirements** 7
 - Tanium dependencies 7
 - Tanium™ Module Server 7
 - Endpoints 8
 - Host and network security requirements 8
 - Ports 8
 - Security exclusions 8
 - User role requirements 10
- Installing End-User Notifications** 13
 - Before you begin 13
 - Import End-User Notifications with default settings 13
 - Import End-User Notifications with custom settings 14
 - Upgrade End-User Notifications 14
 - Verify End-User Notifications version 14
- Configuring End-User Notifications** 15

Configure End-User Notifications	15
Configure service account	15
Configure End-User Notifications action group	15
Customize the End-User Self Service Client	15
Set up End-User Notifications users	15
Initialize endpoints	16
Customizing the End-User Self Service interface	17
Create a profile	17
Prioritize profiles	17
View, edit, or delete profiles	18
Troubleshooting End-User Notifications	19
Collect logs	19
Problem: End user notifications are not displayed	19
Uninstall End-User Notifications	19
Contact Tanium Support	19

End-User Notifications overview

End-User Notifications is a shared service that is used by other Tanium products, such as Tanium Deploy, Tanium™ Patch, and Tanium™ Enforce to notify users about system actions. It is also used by Deploy for self service capabilities.

End-User Notifications

When you use End-User Notifications with other solutions, you can create notification messages to notify the user of system actions or user requirements.

End-User Self Service

When you use End-User Notifications with Deploy, you can configure the Self Service Client application for Windows endpoints. With the Self Service Client application, you can publish software to endpoints so that users can install software on their own without the need for IT to install for them. For more information, see [Customizing the End-User Self Service interface on page 17](#).

Integration with other Tanium products

End-User Notifications integrates with other Tanium products to provide additional features.

Deploy

End-User Notifications is used by Deploy to notify users about deployments to Windows and macOS endpoints, and to configure End-User Self Service capabilities to Windows endpoints. You can create a notification message with your deployment to notify the user that the system is about to begin a deployment, has completed a deployment, and if postponements are enabled, to give the user the option to postpone the deployment or restart now. For more information, see [Tanium Deploy User Guide: Windows and macOS endpoint restarts](#) or [Tanium Deploy User Guide: Using the Self Service Client application](#).

Patch

End-User Notifications is used by Patch to notify users about deployments to Windows endpoints. You can create a notification message with your deployment to notify the user that the system is about to begin a deployment, has completed a deployment, and if postponements are enabled, to give the user the option to postpone the deployment or restart now. For more information, see [Tanium Patch User Guide: Endpoint restarts](#).

Enforce

End-User Notifications is used by Enforce to instruct users to enable encryption, and to notify users before a restart. You can create a notification message in the FileVault policy that displays either at log out or during the next log in. Users can dismiss the message multiple times if the FileVault policy allows it. For more information, see [Tanium Enforce User Guide: Create a FileVault policy](#). You can also create a notification message that displays to the user after a BitLocker policy is enforced. The message notifies users before the computer is restarted to prepare their drives for encryption. For more information, see [Tanium Enforce User Guide: Create a BitLocker policy](#).

Getting started

Step 1: Install and configure Tanium End-User Notifications

Install and configure Tanium End-User Notifications.

For more information, see [Installing End-User Notifications on page 13](#).

Step 2: Configure endpoint restart notifications for Deploy or Patch deployments

Configure endpoint restart notifications for Deploy or Patch deployments.

For more information, see [Tanium Deploy User Guide: Deploying packages and bundles](#) or [Tanium Patch User Guide: Deploying patches](#).

Step 3: Configure notifications for Enforce FileVault or BitLocker policies

Configure notifications for Enforce FileVault or BitLocker policies.

For more information, see [Tanium Enforce User Guide: Create a FileVault policy](#) or [Tanium Enforce User Guide: Create a BitLocker policy](#).

Step 4: Customize the end-user interface to use with Deploy

Customize the end-user interface to use with Deploy.

For more information, see [Customizing the End-User Self Service interface on page 17](#).

End-User Notifications requirements

Review the requirements before you install and use End-User Notifications.

Tanium dependencies

In addition to a license for the End-User Notifications product module, make sure that your environment also meets the following requirements.

Component	Requirement
Tanium™ Core Platform	7.2 or later.
Tanium™ Client	<p>Any supported version of Tanium Client. For the Tanium Client versions supported for each OS, see Tanium Client Management User Guide: Client version and host system requirements.</p> <p>If you use a client version that is not listed, certain product features might not be available, or stability issues can occur that can only be resolved by upgrading to one of the listed client versions.</p>
Tanium solutions	<p>If you selected Tanium Recommended Installation when you installed End-User Notifications, the Tanium Server automatically installed all your licensed solutions at the same time. Otherwise, you must manually install the Tanium solutions that End-User Notifications requires to function, as described under Tanium Console User Guide: Import, re-import, or update specific solutions.</p> <p>Tanium solutions at the following minimum versions are required:</p> <ul style="list-style-type: none">• Tanium Endpoint Configuration 1.2 or later (installed as part of Tanium Client Management 1.5 or later) <p>The following Tanium solutions are optional, but End-User Notifications requires the specified minimum versions to work with them:</p> <ul style="list-style-type: none">• Tanium Deploy 1.3 or later for end-user notifications or end-user self service• Tanium Patch 2.1 or later for end-user notifications• Tanium Enforce 1.5 or later for end-user notifications for BitLocker or FileVault policies• Tanium Trends 3.6 or later
Computer groups	<p>When you first sign in to the Tanium Console after installing the Tanium Server, the server automatically imports the computer groups that End-User Notifications requires: <code>All Computers</code>.</p>

Tanium™ Module Server

End-User Notifications is installed and runs as a service on the Module Server host computer. The impact on the Module Server is minimal and depends on usage.

Endpoints

End-User Notifications supports the following client operating systems:

Operating System	Version	Notes
Windows Server	Windows Server 2008 R2 Service Pack 1 or later	Windows Server Core not supported.
Windows Workstation	<ul style="list-style-type: none">Windows 10Windows 8.1Windows 8Windows 7 Service Pack 1 or later	Windows 7 Service Pack 1 requires Microsoft KB2758857 .
macOS	<ul style="list-style-type: none">macOS 11.0 Big SurmacOS 10.15 CatalinamacOS 10.14.6 MojavemacOS 10.13.6 High Sierra	<ul style="list-style-type: none">Supported for Deploy software deployments to endpoints.Supported for Enforce FileVault policies.

Host and network security requirements

Specific ports and processes are needed to run End-User Notifications.

Ports

The following ports are required for End-User Notifications communication.

Source	Destination	Port	Protocol	Purpose
Module Server	Module Server (loopback)	17476	TCP	Internal purposes; not externally accessible



BEST PRACTICE

Configure firewall policies to open ports for Tanium traffic with TCP-based rules instead of application identity-based rules. For example, on a Palo Alto Networks firewall, configure the rules with service objects or service groups instead of application objects or application groups.

Security exclusions

If security software is in use in the environment to monitor and block unknown host system processes, your security administrator must create exclusions to allow the Tanium processes to run without interference. For a list of all security exclusions to define across Tanium, see [Tanium Core Platform Deployment Reference Guide: Host system security exclusions](#).

End-User Notifications security exclusions

Target Device	Notes	Exclusion Type	Exclusion
Module Server	Required when Endpoint Configuration is installed	Process	<Module Server>\interdependence-configuration-service\taniumEndpointConfigService.exe
		Process	<Module Server>\services\end-user-notifications-service\node.exe
		Process	<Module Server>\services\twsm-v1\twsm.exe
Windows endpoints	7.2.x clients	Process	<Tanium Client>\Python27\TPython.exe
	7.4.x clients	Process	<Tanium Client>\Python38\TPython.exe
	64-bit OS versions	Process	%programfiles(x86)%\Tanium\Tanium End User Notification Tools\UserSessionProxy.exe
	32-bit OS versions	Process	%programfiles%\Tanium\Tanium End User Notification Tools\UserSessionProxy.exe
	64-bit OS versions	Process	%programfiles(x86)%\Tanium\Tanium End User Notification Tools\bin\end-user-notifications.exe
	32-bit OS versions	Process	%programfiles%\Tanium\Tanium End User Notification Tools\bin\end-user-notifications.exe
	exclude from on-access or real-time scans (64-bit OS versions)	Folder	%programfiles(x86)%\Tanium\Tanium End User Notification Tools
	exclude from on-access or real-time scans (32-bit OS versions)	Folder	%programfiles%\Tanium\Tanium End User Notification Tools
	Folder	%programdata%\Tanium	

End-User Notifications security exclusions (continued)









Target Device	Notes	Exclusion Type	Exclusion
macOS endpoints	7.2.x clients	Process	<Tanium Client>/python27/bin/pybin
	7.4.x clients	Process	<Tanium Client>/python38/bin/pybin
		Process	/Library/Tanium/EndUserNotifications/bin/end-user-notifications.app
		Folder	/Library/Tanium/EndUserNotifications

User role requirements













The following tables list the role permissions required to use End-User Notifications. To review a summary of the predefined roles, see [Set up End-User Notifications users on page 15](#).

For more information about role permissions and associated content sets, see [Tanium Core Platform User Guide: Managing RBAC](#).

End-User Notifications user role permissions

Permission	End-User Notifications Administrator ^{1,2}	End-User Notifications Endpoint Configuration Approver ^{1,2}	End-User Notifications Operator ^{1,2}	End-User Notifications Read Only User ^{1,2}
End-User Notifications Endpoint Configuration APPROVE: Approve End-User Notifications items for Endpoint Configuration REGISTER: Access to register with Endpoint Configuration	 REGISTER	 APPROVE		
End-User Notifications Module Read and write access to the End-User Notifications shared service	 READ WRITE	 READ	 READ	 READ

















End-User Notifications user role permissions (continued)

Permission	End-User Notifications Administrator ^{1,2}	End-User Notifications Endpoint Configuration Approver ^{1,2}	End-User Notifications Operator ^{1,2}	End-User Notifications Read Only User ^{1,2}
End-User Notifications Operator Module Write access to a subset of the End-User Notifications shared service	 WRITE		 WRITE	
End-User Notifications Use API Access to the End-User Notifications API	 EXECUTE	 EXECUTE	 EXECUTE	 EXECUTE
Endusertnotifications View the End-User Notifications shared service	 SHOW	 SHOW	 SHOW	 SHOW

¹ This role provides module permissions for Tanium Endpoint Configuration. You can view which Endpoint Configuration permissions are granted to this role in the Tanium Console. For more information, see [Tanium Endpoint Configuration User Guide: User role requirements](#).

² This role provides module permissions for Tanium Interact. You can view which Interact permissions are granted to this role in the Tanium Console. For more information, see [Tanium Interact User Guide: Tanium Data Service permissions](#).

Provided End-User Notifications administration and platform content permissions

Permission	Permission Type	End-User Notifications Administrator ¹	End-User Notifications Endpoint Configuration Approver ¹	End-User Notifications Operator ¹	End-User Notifications Read Only User ¹
Computer Group	Administration	 READ	 READ	 READ	 READ
User	Administration	 READ		 READ	
User Group	Administration	 READ	 READ	 READ	 READ
Action	Platform Content	 WRITE		 WRITE	

Provided End-User Notifications administration and platform content permissions (continued)

Permission	Permission Type	End-User Notifications Administrator ¹	End-User Notifications Endpoint Configuration Approver ¹	End-User Notifications Operator ¹	End-User Notifications Read Only User ¹
Approve Action	Platform Content	✓ SPECIAL	✗	✓ SPECIAL	✗
Own Action	Platform Content	✓ READ	✗	✓ READ	✗
Package	Platform Content	✓ READ WRITE	✗	✓ READ WRITE	✗
Plugin	Platform Content	✓ READ EXECUTE	✓ READ EXECUTE	✓ READ EXECUTE	✓ READ EXECUTE
Saved Question	Platform Content	✓ READ WRITE	✗	✓ READ WRITE	✗
Sensor	Platform Content	✓ READ	✓ READ	✓ READ	✓ READ

You can view which content sets are granted to any role in the Tanium Console.

¹ This role provides content set permissions for Tanium Endpoint Configuration. You can view which Endpoint Configuration content sets are granted to this role in the Tanium Console. For more information, see [Tanium Endpoint Configuration User Guide: User role requirements](#).

For more information and descriptions of content sets and permissions, see [Tanium Core Platform User Guide: Users and user groups](#).

Installing End-User Notifications

Use the **Solutions** page to install End-User Notifications and choose either automatic or manual configuration:

- **Automatic configuration with default settings** (Tanium Core Platform 7.4.2 or later only): End-User Notifications is installed with any required dependencies and other selected products. After installation, the Tanium Server automatically configures the recommended default settings. This option is the best practice for most deployments. For more information about the automatic configuration for End-User Notifications, see [Import End-User Notifications with default settings on page 13](#).
- **Manual configuration with custom settings**: After installing End-User Notifications, you must manually configure required settings. Select this option only if End-User Notifications requires settings that differ from the recommended default settings. For more information, see [Import End-User Notifications with custom settings on page 14](#).

Before you begin

- Read the [release notes](#).
- Review the [End-User Notifications requirements on page 7](#).
- If you are upgrading from a previous version, see [Upgrade End-User Notifications on page 14](#).

Import End-User Notifications with default settings

(Tanium Core Platform 7.4.5 or later only) You can set the module action group to target the **No Computers** filter group by enabling restricted targeting before importing the module. This option enables you to control tools deployment through scheduled actions that are created during the import and that target the module action group. For example, you might want to test tools on a subset of endpoints before deploying the tools to all endpoints. In this case, you can manually deploy the tools to an action group that you configured to target only the subset. To configure an action group, see [Tanium Console User Guide: Managing action groups](#). To enable or disable restricted targeting, see [Tanium Console User Guide: Dependencies, default settings, and tools deployment](#).

When you import End-User Notifications with automatic configuration, the following default settings are configured:

Setting	Default value
Action group	<ul style="list-style-type: none">• Restricted targeting disabled (default): <code>ALL Computers</code> computer group• Restricted targeting enabled: <code>No Computers</code> computer group
Service account	<p>The service account is set to the account that you used to import the module.</p> <p>Configuring a unique service account for each Tanium solution is an extra security measure to consider in consultation with the security team of your organization. See Configure service account on page 15.</p>
End-User Notifications configurations	<ul style="list-style-type: none">• A default End-User Notifications profile is created.• The End-User Notifications tools are distributed to endpoints.

To import End-User Notifications and configure default settings, be sure to select the **Apply All Tanium recommended configurations** check box while performing the steps in [Tanium Console User Guide: Import all modules and services](#). After the import, verify that the correct version is installed. For more information, see [Verify End-User Notifications version on page 14](#).

Import End-User Notifications with custom settings

To import End-User Notifications without automatically configuring default settings, be sure to clear the **Apply All Tanium recommended configurations** check box while performing the steps in [Tanium Console User Guide: Import, re-import, or update specific solutions](#). After the import, verify that the correct version is installed. For more information, see [Verify End-User Notifications version on page 14](#).

To configure the service account, see [Configure service account on page 15](#).

To configure the End-User Notifications action group, see [Configure End-User Notifications action group on page 15](#).


To customize notifications, see [Customize the End-User Self Service Client on page 15](#).

Upgrade End-User Notifications

For the steps to upgrade End-User Notifications, see [Tanium Console User Guide: Import all modules and services](#). After the upgrade, verify that the correct version is installed. For more information, see [Verify End-User Notifications version on page 14](#).

Verify End-User Notifications version

After you import or upgrade End-User Notifications, verify that the correct version is installed:

1. Refresh your browser.
2. From the Main menu, go to **Administration > Shared Services > End-User Notifications** to open the End-User Notifications **Overview** page.
3. To display version information, click Info .

Configuring End-User Notifications

If you did not install End-User Notifications with the **Apply All Tanium recommended configurations** option, you must enable and configure certain features.

Configure End-User Notifications


Configure service account

The service account is a user that runs background processes for End-User Notifications. This user requires the **Content Administrator** and **End-User Notifications Administrator** roles or the **Tanium Administrator** role.

For more information about End-User Notifications permissions, see [User role requirements on page 10](#).



If you imported End-User Notifications with default settings, the service account is set to the account that you used to perform the import. Configuring a unique service account for each Tanium solution is an extra security measure to consider in consultation with the security team of your organization.

1. On the End-User Notifications **Home** page, click Settings  and open the **Service Account** tab.
2. Update the service account settings and click **Submit**.

Configure End-User Notifications action group

The End-User Notifications action group controls what endpoints receive End-User Notification Tools. All targeted Windows and macOS endpoints receive tools.

1. From the Main menu, go to **Administration > Actions > Action Groups**.
2. In the list of action groups, click **Tanium End-User Notifications**.
3. Click **Edit**, select computer groups to include in the action group, and click **Save**.

Customize the End-User Self Service Client

Add a company logo and relevant information to personalize the End-User Self-Service experience.

You must create at least one End-User Notifications profile. For more information about creating a profile, see [Create a profile on page 17](#).

Set up End-User Notifications users

You can use the following set of predefined user roles to set up End-User Notifications users.

To review specific permissions for each role, see [User role requirements on page 10](#).

For more information about assigning user roles, see [Tanium Core Platform User Guide: Manage role assignments for a user](#).

End-User Notifications Administrator

Assign the **End-User Notifications Administrator** role to users who manage the configuration and deployment of End-User Notifications functionality to endpoints.

End-User Notifications Endpoint Configuration Approver

Assign the **End-User Notifications Endpoint Configuration Approver** role to a user who approves or rejects End-User Notifications configuration items in Tanium Endpoint Configuration. This role can approve, reject, or dismiss End-User Notifications configuration changes.

End-User Notifications Endpoint Configuration Operator


Assign the **End-User Notifications Operator** role to users who manage most configurations and deployment of End-User Notifications functionality to endpoints.

End-User Notifications Endpoint Configuration Read Only User

Assign the **End-User Notifications Read Only User** role to users who need visibility into End-User Notifications settings but do not need rights to update them.

Initialize endpoints

End-User Notifications installs a set of tools on each endpoint that you have targeted. Initializing endpoints configures the End-User Notifications Tools to be installed on any compatible endpoint in the End-User Notifications action group. You must complete this procedure any time the action group is changed.

1. On the End-User Notifications **Overview** page, click Help , and then click **Support** if needed.
2. Click **Initialize Endpoints** and confirm your action.



After deploying the tools for the first time, endpoints can take up to four hours to display status.

Customizing the End-User Self Service interface

To customize the End-User Self Service interface to use with Deploy, create additional End-User Notifications profiles. Each profile defines a set of configurations, rules, or parameters that applies to one or more computer groups.

Create a profile

1. From the End-User Notifications menu, click **Profiles** and then click **Create Profile**.
2. Provide a name and optional description.
3. Select target computers.



Only one profile can apply to an endpoint.

NOTE

4. Provide a title and upload a logo file.
5. (Optional) Select **Enable End-User Self Service**.
 - a. Provide a welcome message to display in the self-service dashboard on endpoints.
 - b. Select installation options.
6. (Optional) Select **Enable Additional Languages**.
 - a. Select a language and provide a translated title and welcome message.
 - b. (Optional) Click **Add Language** to add more languages.



By default, the Self Service Client application displays content in the system language on the endpoints. If you enable additional languages, the user can select other languages to display.

NOTE

7. Click **Submit**.

After you customize the End-User Self Service interface, you can create a self service profile in Deploy. For more information, see [Tanium Deploy User Guide: Using the Self Service Client application](#).

Prioritize profiles

If you have more than one profile, you can prioritize them. Endpoints targeted with more than one profile use the settings from the highest priority profile.

1. From the End-User Notifications menu, click **Profiles** and then click **Prioritize**.
2. Drag and drop a profile to reprioritize it. End-User Notifications automatically adjusts the priority numbers for the other profiles and reorders the list by priority.
3. Click **Confirm**.

View, edit, or delete profiles

To view profiles, click **Profiles** from the End-User Notifications menu. You can also view them from the **Profiles** section of the End-User Notifications **Home** page.

To edit a profile, click the name of the profile.


To delete a profile, select a profile and click **Delete**.

Troubleshooting End-User Notifications

To collect and send information to Tanium for troubleshooting, collect logs and other relevant information.

Collect logs

The information is saved as a ZIP file that you can download with your browser.

1. From the End-User Notifications **Home** page, click Help , then the **Support** tab.
2. Click **Collect**.
3. When **Status** indicates that the package is collected, click **Download**.
4. Contact Tanium Support to determine the best option to send the ZIP file. For more information, see [Contact Tanium Support on page 19](#).


End-User Notifications maintains logging information in the log file in the `\Program Files\Tanium\Tanium Module Server\services\end-user-notifications-files\logs` directory.

Problem: End user notifications are not displayed

If end user notifications are not being displayed on the endpoints:

1. Verify that the Tanium End-User Notifications solution is installed. For more information, see [Installing End-User Notifications on page 13](#).
2. Verify that endpoints have the end user notification tools by asking the question `End-User Notifications - Has Tools`.
3. Verify that required security exclusions for End-User Notifications are configured in any security software. For more information, see [Security exclusions on page 8](#). For assistance in ensuring exclusions have taken effect, [Contact Tanium Support on page 19](#).

Uninstall End-User Notifications

1. From the Main menu, go to **Administration > Configuration > Solutions**.
2. In the **Content** section, select the **End-User Notifications** row.
3. Click Delete Selected  and then click **Uninstall** to complete the process.

Contact Tanium Support

To contact Tanium Support for help, sign in to <https://support.tanium.com>.